



16 Sources to 16 Displays. Crosspoint Matrix.



GEF-DVI-16416-PB

Overview

Simplify the process of routing multiple DVI sources by giving the ability to route sources without losing quality or resolution. Route 16 sources to 16 digital monitors using the GefenPRO 16x16 DVI Matrix. The Matrix provides a simple, reliable and highly effective method of streamlining any installation using multiple sources and outputs. Four methods are available for controlling the GefenPRO 16x16 DVI Matrix: Front panel buttons, IR remote, RS-232 interface, IP control, or the Gefen Keyboard Controller software. The Gefen Syner-G PC software provides easy firmware updates for selected Gefen products

How It Works

The GefenPRO 16x16 DVI Matrix has 16 DVI inputs and 16 DVI outputs. Using the supplied DVI cables, connect 16 sources to the DVI input ports on the GefenPRO 16x16 DVI Matrix. Connect the GefenPRO 16x16 DVI Matrix's 16 DVI outputs to the monitors. Plug in the power cord and power on the GefenPRO 16x16 DVI Matrix. The connected monitors will show video according to the routing selection.

Note: The GefenPRO 16x16 DVI Matrix with Front Panel Push Button Control only supports DVI-D although the DVI connectors use DVI-I connectors.

Features*:

- Supports resolutions up to 1920 x 1200
- Front-panel push buttons for local switching
- Front-panel LCD Display
- Switching is controlled via front panel buttons, IR remote, IP, or RS-232 commands
- Compatible with the Gefen Keyboard Controller software
- Advanced EDID management
- Programmable routing presets
- Standby mode
- Output masking control
- IP control and configuration with built-in Web server
- Easy firmware upgrades using Gefen Syner-G software, download able from Gefen website
- Internal power supply
- Rack-mountable

Specifications*:

- Maximum Pixel Clock: 165MHz
- Input Video Signal: 1.2V p-p
- Input DDC Signal: 5V p-p (TTL)
- Video Input Connectors: (16) DVI-I 29-pin, female (digital only)
- Video Output Connectors: (16) DVI-I 29-pin, female (digital only)
- RS-232 Port: DB-9, female
- IR Extender Input: 3.5 mm mini-stereo jack
- IP Control Port: RJ-45, Shielded
- Power Supply: 100 - 240V AC (Internal)
- Power Consumption: 90W (max.)
- Dimensions: 17.2" W x 12" D x 3.5" H
- Shipping Weight: 30 lbs.

Gefen, LLC
20600 Nordhoff Street, Chatsworth CA 91311
Tel. (818) 772-9100 (800) 545-6900 Fax (818) 772-9120
www.gefen.com

*Specifications subject to change without notice.
All trademarks are the properties of their respective owners.

REV. A2