

New Product PU-8H8HBTE-4K22

8 x 8 HDMI HDBaseT™ Matrix (5Play™ including LAN serving, 4K resolution support & HDCP2.2)



HDCP2.2 5Play™ HDBT® HDMI®

The PU-8H8HBTE-4K22 8 by 8 HDMI Matrix over CAT5e/6/7 supports the transmission of video (resolutions up to 4K2K Full HD, HDCP 2.2) and multi-channel digital audio from 8 HDMI sources to 8 outputs. It supports high resolution digital audio formats such as LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio as well as 3D content that can be displayed when connecting a 3D TV and 3D source.

This matrix features control via manual selection buttons, IR, RS-232, Telnet or Web GUI. CYP provide control drivers for all the major control systems. This unit also supports RS232 pass-through to the receivers.

The PU-8H8HBTE-4K22 is designed to be used with any of the HDBaseT receivers that can utilise the PoE capabilities of the matrix.

The LAN serving capabilities of the matrix provide network connections in every zone.

FEATURES

- HDCP 2.2 Compliant
- Supports resolutions VGA~WUXGA, 480i~1080p, 4K UHD@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2), 4K UHD@60Hz (YUV 4:2:0), 4K/2K@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2) and 4K/2K@60Hz (YUV 4:2:0) dependent upon the output display's EDID settings
- Supports uncompressed video/audio up to 10.2Gbps
- Supports LPCM 7.1CH, Dolby TrueHD, Dolby Digital Plus and DTS-HD Master Audio transmission
- Supports 1080p distances up to 100 meters through CAT6/7 cables
- Supports 4K UHD distances up to 100 meters via CAT6a/7 cables
- Supports 3D signal display dependent upon the output display EDID settings
- Supports PoC (Power over Cable) on compatible receivers only
- Supports bi-directional IR from input and output locations
- Supports RS-232, remote control, on-panel control and IP Control (Telnet & Web GUI)
- Supports LAN serving function through the LAN port
- 2U size design
- Supports external and internal EDID settings
- Supports RS-232 for Matrix Control, plus RS-232 pass-through: Third-party devices can be controlled in each zone via RS-232 from the head-end to the receiver, or head-end devices can be controlled via RS-232 from any receiver in any zone.

SPECIFICATIONS

- Input:** 8x HDMI (8x HDMI Uncompressed AV and Data), 9x 3.5mm Stereo mini-jack (9x Infra Red Receiver), 1x RJ45 (1x LAN Serving / IP Control), 1x 9pin Dsub (1x RS-232 Data), 1x USB Mini B (1x Service Port Proprietary Data)
- Output:** 8x RJ45 (8x HDBaseT HDMI & Proprietary Data), 9x 3.5mm Stereo mini-jack (9x Infra Red Emitter)
- Compatible Receivers:** PU-507TX, PU-1109RX, PU-507WPRX
- Power:** 24V/6.25A DC (US/EU standards, CE/FCC/UL certified)
- PoC Power:** 24V/6.25A DC (US/EU standards, CE/FCC/UL certified)
- Dimensions:** 438mm (W) x 249mm (D) x 88mm (H)
- Gross Weight:** 5700g **Net Weight:** 4370g
- Packaging:** Boxed

